

H2O INC

INTERNATIONAL H2O INC

1(888) 982-8311

sales@internationalh2o.com www.internationalh2o.com

18267 NE 4th Ct North Miami Beach Fl 33162





Efficient, Highly Reliable, and just the Right capacity Specifications as a work horse unit; the H2O-2200 is a fully mechanical Hold, Cold, and Ambient Dispenser with an LG Compressor and a 2 Gallon Cold Tank.

Featuring a redesigned new to market dual function mechanical paddle, the H2O-2200 is able to dispense both hot and ambient water from a single spigot, allowing for the classic mechanical 2 spigot / paddle design while being able to deliver 3 temperatures of water.

SPECIFICATIONS & FEATURES

Dimensions 14" W x 14" L x 48" H Weight 54 lbs 2 Gallons Cold Tank

Hot Tank 1 Gallon Cooling Rate 3 Gal/hour 37-50°F Heating Rate 2.8 Gal/hour 180°F

LG Compressor Anti-Microbial Panels Hot & Cold Water Hot Water Safety Lock

Hot Power Consumption 1000W Cold Power Consumption 100W 110V~127V AC / 50-60Hz Refrigerant R134A Climate Class T

USA Final Assembly & Quality Control

2-Stage Filtration

Stage 1: Sediment Stage 2: Post Carbon Filter

3-Stage Filtration

Stage 1: Sediment Stage 2: Pre-Carbon

Stage 3: Post Carbon Filter

4-Stage UltraFiltration

Stage 1: Sediment

Stage 2: Pre-Carbon

Stage 3: Ultra-Filtration Membrane

Stage 4: Post Carbon Filter

Reverse Osmosis Purification

Stage 1: Sediment Filter Stage 2: Activated Carbon Filter

Stage 3: 100 GDP Reverse Osmosis

Membrane

Stage 4: Post Carbon Filter

AVAILABLE IN:



black

