

# H2O-400

**H2O INC**  
INTERNATIONAL H2O INC  
1(888) 982-8311  
sales@internationalh2o.com  
www.internationalh2o.com

18267 NE 4th Ct  
North Miami Beach FL 33162

# H2O



A sleek, industry leading reliability, minimal foot print tower unit at an amazing price point; the H2O-400 is perfect for low to mid traffic applications in commercial and residential settings.

The H2O-400 dispenses both hot and cold water, and is equipped with an LG compressor, surgical stainless steel hot and cold tanks. It is available in Shell, Reverse Osmosis, and Ultra Filtration.

## SPECIFICATIONS & FEATURES

12" W x 5" L x 17" H  
Dimensions: 11" W x 14.75" L x 43.75" H  
Weight: 75 lbs  
Flow Rate: 7.5 Gallons Per Minute (w/ Tank)  
Cold Tank: 1 gallon  
Lead Tank: 1 gallon  
Hot Tank: 1.5 gallon  
Cooling Rate: 1.5 gal/hour 37-50°F  
Heating Rate: 1.3 gal/hour 180°F

### Available in:

- Reverse Osmosis Purification w/alkaline Reverse Osmosis Purification
- Reverse Osmosis Purification
- Anti-Microbial Panels
- Hot & Cold Water
- Hot Water Safety Lock

Hot Power Consumption 1000W  
Cold Power Consumption 100W  
110V~127V AC / 50-60Hz  
Refrigerant R134A  
Climate Class T  
**USA** Final Assembly & Quality Control

## 2-Stage Filtration

Stage 1: Sediment  
Stage 2: Post Carbon Filter

## 3-Stage Filtration

Stage 1: Sediment  
Stage 2: Pre-Carbon  
Stage 3: Post Carbon Filter

## 4-Stage UltraFiltration

Stage 1: Sediment  
Stage 2: Pre-Carbon  
Stage 3: Ultra-Filtration Membrane  
Stage 4: Post Carbon Filter

## Reverse Osmosis Purification

Stage 1: Sediment Filter  
Stage 2: Activated Carbon Filter  
Stage 3: 100 GDP Reverse Osmosis Membrane  
Stage 4: Post Carbon Filter

AVAILABLE IN:



white black